



LA30 - S - DC12V - O

Relay Type: _____

Sealing:- S: Plastic Sealed Type _____

Coil Voltage :- DC: 6~24V _____

Casing:- O: Without Casing Nil: With Casing _____

Features	Dimension L * W * H (mm)	26.5 * 21 * 21			
	Terminal Type	PCB			
	Weight	21 gm Approximately			
Contact Data	Contact Form/Resistance	1C 100mΩ @ 1A, 6VDC			
	Contact Material	Ag Alloy			
	Contact Capacity	40A / 14VDC			
Coil Data	Coil Voltage (DC)	6 ~ 24VDC			
	Coil Power Consumption	1.6W			
	Coil Specification	Coil Voltage	Coil Resistance (Ω) ± 10%	Pull in Voltage (VDC)	Drop Out Voltage (VDC)
		12 VDC	90	70%	5%
	24 VDC	362	70%	5%	
General Data	Dielectric Strength	500VAC (Between open Contacts)			
		750VAC (Between coil & Contacts)			
	Insulation Resistance	100MΩ 500VDC			
	Electrical Life	1 x 10 ⁵			
	Mechanical Life	1 x 10 ⁷			
Operating Temperature	- 40 °C ~ + 85°C				
Mounting Diagram					
Application	Wiper, Alarm System, Power Antenna, Power Window, Towing Bar, Air Conditioning System, Lamp Control System, etc.				