



Type:-B



Type:-A

Relay Type:- LP11 DC12V  
 Terminal Type:- Nil Solder P Plug In  
 Coil Voltage:- DC/AC

Model		LP 11			
Features	Dimension L * W * H (mm)	58.8 * 33 * 28			
	Terminal Type	Solder/Plug in			
	Weight	73 gm Approximately			
Contact Data	Contact Form	1C			
	Contact Material	Ag Alloy			
	Contact Capacity	7A @ 250VAC /28VDC			
	Contact Resistance	100mΩ			
Coil Data	Coil Voltage ( DC)	6 ~ 220 VDC			
	Coil Voltage ( AC)	6 ~ 380 VAC			
	Coil Power Consumption	DC: 2.0W AC 3.5VA			
	Coil Specification	Coil Voltage	Coil Resistance (Ω) ±10%	Pull in Voltage (Max)	Drop Out Voltage (Min)
		12 VDC	160	75 %	10 %
24 VDC		500	75%	10 %	
240 VAC		10000	80 %	30 %	
General Data	Dielectric Strength	1200 VAC @ 50 Hz / Min (Between Open Contacts)			
		1500 VAC @ 50 Hz / Min ( Between Coil & Contacts)			
	Insulation Resistance	500 MΩ			
	Electrical Life	1 x 10 <sup>5</sup>			
	Mechanical Life	1 x 10 <sup>7</sup>			
Operating Temperature	- 25 °C ~ + 55°C				
Dimensions					
Application	Vending Machine, Control Equipments, Cooking Appliances etc.				